

Contact: Wayne Comley

Contact Info: Office: (08) 8376 9098

Mobile: 0419 846 557

email: wayne@roofscapes.com.au



“Bullnose” verandah with
separate “Bullnose” carport.

Specification

- Posts: 112 mm x 112 mm
Hammersmith brand “turned”.
- Half Posts: Hammersmith brand
“turned”.
- Fascia: 230 mm x 42 mm LOSP
treated pine, with old style “beaded”
bottom edge.
- Wall Plate: 90 mm x 42 mm LOSP
treated pine.
- Curved rafters: Cut from 45 mm
thickness L.V.L. beams.
- Roofing: 0.60 mm “Ironstone” pre-
painted Colorbond steel.
- Gutters: “OG” profile “Hunter Red” pre-
painted “Colorbond steel”.
- Hip capping: “Acrylead” formed over
PVC electrical conduit (to maintain
integrity of rolltop)



The owners approached us to quote on re-roofing the home as well as constructing a new verandah and carport.

They wanted to replace the existing verandah, (a flat roof style with large columns) with a bullnose style that the home originally featured.

The owners arranged for a new verandah floor, including traditional slate edging and tessellated tiles.

We fitted authentic reproduction lace frieze and corners.



The bullnose carport has Hammersmith brand “turned” posts; including the posts either side of the panel-lift door opening. The door tracks are mounted on a timber plate fixed to the inside of the “turned” posts.

The “hip” at the front end is set back the same width as the front verandah so that the slope on bullnose roofing at the front matches the slope on the bullnose verandah.

There is a “Barge” rear end with “Hardiflex” fibre cement sheet infil between the fascia and the bullnose shaped rafter.